



# TWO POST SUPER ASYMMETRIC LIFT


*With extremely long carriages, direct drive cylinders and advance features.*




30-210HX  
30-210HHX

## SPECIFICATIONS


		30-210HX	30-210HHX
Lifting Capacity		10,000lbs (4500kg)	10,000lbs (4500kg)
Lifting Time		57S	63S
Lifting Height	A	71 1/2" ~ 80 1/2" (1815~2044mm)	78 3/4"~87 3/4" (2000~2229 mm)
Overall Height	B	144" (3658mm)	157"~168" (3988~4267 mm)
Overall Width	C	135"/142 7/8" (3428/3628mm)	135"/142 7/8" (3428/3628mm)
Drive-Thru Clearance	D	99 1/4"/107" (2520/2720mm)	99 1/4"/107" (2520/2720mm)
Width Between Columns	E	112 1/4"/120" (2850/3050mm)	112 1/4"/120" (2850/3050mm)
Minimum Pad Height	F	3 1/2"(90mm)	3 1/2"(90mm)
Motor		2.0HP,220V/60Hz,single phase	
Gross Weight		1,620lbs(735kg)	1,744lbs(791 kg)



30-210HX



30-210HHX



# TWO-POST SUPER ASYMMETRIC LIFT

*The professional lifts model OHX Series are designed with asymmetric arms but also can be configured with symmetric, Height & Width adjustment, fitting for low ceiling (model 30-210HHX) and high ceiling but with extremely high lifting (model 30-210HX).*

- ✓ 10,000 lbs capacity.
- ✓ Dual hydraulic cylinders, designed and made on high standard, high quality seals.
- ✓ Super Asymmetric arms allow to load different vehicles in an asymmetric or symmetric configuration.
- ✓ 3/8" aircraft quality cable is used for synchronization.
- ✓ Self-lubricating UHMW Polyethylene sliders and bronze bush.
- ✓ Single-point safety release, and dual safety design.
- ✓ Clearfloor design, provide unobstructed floor space.
- ✓ Overhead safety shut-off device.
- ✓ Automatic arm restraints keep the arms locked in their proper positions.
- ✓ Adjustable heights for OHX-10H
- ✓ Stackable adapters 1.5", 2.5", 5" as standard.
- ✓ Detachable foot guard and tool tray.



The extremely long carriages is to reduce the force to columns. In other word, it is durable and reliable!

The carriages is two times or more longer than other products in the market.




**Lifting arm lock** automatic release device, high strength gear rack, more stable and safer.



**Super-Asymmetric arms**

Super asymmetric arms allow you to load different vehicles in an asymmetric or symmetric configuration. Self-lubricating UHMW polyethylene sliders, rubber door guards to protect your vehicle.




**Extension adapters:**

With three different sizes of stackable adapters to adjust the height of rubber pad freely.

## FEATURES




- Single Point safety release makes it easy for the operator to unlock both column locks from one column.



- The top beam is designed with adjustment to fit different width demand. Overhead safety shut-off device prevents vehicle damages.



- Optional Width Extension Kits With these kits the width between posts is adjusted from 2850mm(112-1/4") to 3000mm(118-1/8") Kits No.: 21004(30-210HH) Kits No.: 21005(30-210HHX).



- Optional LED lights for all two post lifts Clear floor two post lift LED light, Kits No.:40101001 plus extension cable 201128.



- Optional Saddle adapters Perfect choice for wide size SUV vehicles and light trucks. Kits No.:20802.

## ASYMMETRIC DESIGN ARMS, OPEN-DOOR CLEARANCE

The OHX series lift features our innovative super asymmetric technology providing the versatility to lift vehicles both symmetrically and asymmetrically upon demand.

The warranty time of the lifts:  
5 years for steel construction,  
3 years for hydraulic parts,  
2 years for electrical components.