


## SPECIFICATIONS

Model		30-4180S	30-4180A
Style		Non-Alignment	Alignment
Lifting Capacity		18,000lbs(8000kg)	18,000lbs(8000kg)
Lifting Time		92S	92S
Overall Length (Inc. Ramps)	A	293 1/4" (7449mm)	292 3/4" (7436mm)
Overall Length(No Inc. Ramps)	B	252 1/4" (6408mm)	252 1/4" (6408mm)
Overall Width	C	137 1/8" (3482mm)	137 1/8" (3482mm)
Width Between Posts	D	122 3/8" (3108mm)	122 3/8" (3108mm)
Lifting Height	E	73 1/2" (1865mm)	75 3/8" (1915mm)
Overall Height	F	86" (2185mm)	86" (2185mm)
Minimum Height	G	7 7/8" (200mm)	9 7/8" (250mm)
Runway Width	H	22" (558mm)	22" (558mm)
Drive-Thru Clearance	I	108 1/4"(2750mm)	108 1/4" (2750mm)
Width Between Runways	J	51 1/4" (1302mm)	51 1/4" (1302mm)
Min. Four Wheel Align	K	/	99 5/8" (2530mm)
Max. Four Wheel Align	L	/	182 5/8" (4640mm)
Max. Two Wheel Align	M	/	209 1/8" (5310mm)
Gross Weight		3,461 lbs(1570kg)	4,429 lbs(2009kg)
Motor		2 HP, 220V/60Hz, single phase	



## FOUR POST TRUCK LIFT

*BEAR Heavy Duty Truck Lifts are newly engineered lifts that makes light work out of heavy lifting.*




30-4180S


## FOUR POST TRUCK LIFT

**BEAR powerful four-post models provide a 18,000 lbs lifting capacity and feature extra wide runways to accommodate a wide variety of vehicle types. With a double locking safety device, heavy duty design and built to latest manufacturing technology, these lifts are more superior in the competitive lift market.**

- ✓ 18,000 lbs lifting capacity;
- ✓ Air-released safety lock for convenient operation and reliability;
- ✓ Mechanical self-locking device and cable-breaking protection;
- ✓ 1/2" aircraft quality cable;
- ✓ Adjustable turnplate blocks to fit various wheel bases on the 30-4180A;
- ✓ Integrated rear slip plates for the 30-4180A
- ✓ Skid proof diamond platform;
- ✓ Hydraulic cylinders are designed to high standards with high quality seals;
- ✓ Strict quality control of cylinders with flow restrictors to keep a constant low speed;
- ✓ The width of platform is 558mm(22") and width between two platforms are 1302mm(51 1/4").
- ✓ Optional Rolling Jacks:  
RJ-10A 10,000lbs capacity with pneumatic pump.



### FEATURES



- Air controlled safety device.




- Adjustable turnplates blocks for the 30-4180A. Optional turnplate. Kits No.: 40101



- New rear-slip ball sets. Optional LED light kits is fitted for every model of BEAR 4-post lifts. LED Kits No.:40102001



- Optional airline kit. Easy to install for all models of rolling jacks with pneumatic pump accessories. Kits No.: 40106



- Optional length extension kits adds an extra 29" (737mm) length to the platform. Kits No.: 41801



- Optional adjustable blocks for alignment 4 post lift. Kits No.: 41803 (used with kits 40801)